



SPRAYZONE.NET
SPRAY BOOTH MANUFACTURING
REFINISHING TECHNOLOGIES

AUTO PREMIUM | AUTO STANDARD | TRUCK BOOTH | OZONE | PREP-STATION | OPEN FACE

▼ | **PRO-TECH F1 SAFETY CABINETS**

PRO-TECH F1 45 | PRO-TECH F1 60





PRO-TECH F1 CABINET 45

PRO-TECH F1 45 | PRO-TECH F1 60

The Pro-Tech F1 safety cabinets help keep flammable or toxic liquids close to the work area in a safe and organized way while limiting employee exposure. These safety cabinets are designed by industrial designers to meet the safety requirements for businesses to handle flammable liquids. This smaller more compact cabinets are convenient where space is limited. All cabinets comply with current OSHA regulations and are designed in accordance with the standards of NFPA.



PRO-TECH F1 CABINET SPECIFICATIONS

CONSTRUCTION

Pre-painted (Yellow In & Out) Panels
Double wall panels insulated 2" thick
Plastic protection for easy handling
45 gallon barrel capacity

COMPLIANCE

OSHA 29 CFR 1910.106 (e)(2)(ii)(b):
Incidental storage or use of flammable and combustible liquids.

(b) The quantity of liquid that may be located outside of an inside storage room or storage cabinet in a building or in any one fire area of a building shall not exceed:

COMPLIANCE

- (1) 25 gallons of Class IA liquids in containers.
- (2) 120 gallons of Class IB, IC, II, or III liquids in containers.
- (3) 660 gallons of Class IB, IC, II, or III liquids in a single portable tank.

OSHA 29 CFR 1910.106 (d)(3)(i&ii):

Design, construction, and capacity of storage cabinets -
(I) Maximum capacity. Not more than 60 gallons of Class I or Class II liquids, nor more than 120 gallons of Class III liquids may be stored in a storage cabinet.

FOR MORE INFORMATION ON ANY OF OUR
BOOTHS PLEASE CALL

1-800-466-1260





SPRAYZONE.NET

SPRAY BOOTH MANUFACTURING
REFINISHING TECHNOLOGIES



PRO-TECH F1 CABINET 60

PRO-TECH F1 45 | PRO-TECH F1 60

The **Pro-Tech F1 60** is the larger version of our safety cabinets. As the Pro-Tech F1 45, this cabinet helps keep flammable or toxic liquids close to the work area in a safe and organized way while limiting employee exposure. These safety cabinets are designed by industrial designers to meet the safety requirements for businesses to handle flammable liquids. All cabinets comply with current OSHA regulations and are designed in accordance with the standards of NFPA.



PRO-TECH F1 CABINET SPECIFICATIONS

CONSTRUCTION

Pre-painted (Yellow In & Out) Panels
Double wall panels insulated 2" thick
Plastic protection for easy handling
60 gallon barrel capacity

COMPLIANCE

OSHA 29 CFR 1910.106 (e)(2)(ii)(b):
Incidental storage or use of flammable and combustible liquids.

(b) The quantity of liquid that may be located outside of an inside storage room or storage cabinet in a building or in any one fire area of a building shall not exceed:

COMPLIANCE

- (1) 25 gallons of Class IA liquids in containers.
- (2) 120 gallons of Class IB, IC, II, or III liquids in containers.
- (3) 660 gallons of Class IB, IC, II, or III liquids in a single portable tank.

OSHA 29 CFR 1910.106 (d)(3)(i&ii):

Design, construction, and capacity of storage cabinets -

(I) Maximum capacity. Not more than 60 gallons of Class I or Class II liquids, nor more than 120 gallons of Class III liquids may be stored in a storage cabinet.





SPRAYZONE.NET

SPRAY BOOTH MANUFACTURING
REFINISHING TECHNOLOGIES

CONTACT |

Toll Free
[800] 466 - 1260

Fax
562 . 790 . 8079

ONLINE |

Website
www.SprayZone.net

E-mail
Spraybooth@SprayZone.net

ADDRESS |

SPRAYZONE.NET
14059 Garfield Ave.
Paramount, CA 90723